



MIL-DTL-38999 Series III Type TVS Connectors TVS Diode Requirement Form

Table V: TVS Diode Requirement Form (Fill out and return)

Connector Pin #		Diode Voltage Code 5.0 – 440	Diode Polarity Bipolar / Unipolar	Diode Wattage 1,500W / 3,000W / 5,000W	Connector Pin #		Diode Voltage Code 5.0 – 440
1	A				44	w	
2	B				45	x	
3	C				46	y	
4	D				47	z	
5	E				48	AA	
6	F				49	BB	
7	G				50	CC	
8	H				51	DD	
9	J				52	EE	
10	K				53	FF	
11	L				54	GG	
12	M				55	HH	
13	N				56	JJ	
14	P				57	KK	
15	R				58	LL	
16	S				59	MM	
17	T				60	NN	
18	U				61	PP	
19	V				62		
20	W				63		
21	X				64		
22	Y				65		
23	Z				66		
24	a				67		
25	b				68		
26	c				69		
27	d				70		
28	e				71		
29	f				72		
30	g				73		
31	h				74		
32	i				75		
33	j				76		
34	k				77		
35	m				78		
36	n				79		
37	p				80		
38	q				81		
39	r				82		
40	s				83		
41	t				84		
42	u				85		
43	v				86		

Note: Enter "No Diode" for unprotected lines

Dimensions in inches (millimeters) and are subject to change without notice.

**MIL-DTL-38999 Series III Type TVS Connectors
TVS Diode Requirement Form**



Diode Polarity Bipolar / Unipolar	Diode Wattage 1,500W / 3,000W / 5,000W	Connector Pin #	Diode Voltage Code 5.0 – 440	Diode Polarity Bipolar / Unipolar	Diode Wattage 1,500W / 3,000W / 5,000W
		87			
		88			
		89			
		90			
		91			
		92			
		93			
		94			
		95			
		96			
		97			
		98			
		99			
		100			
		101			
		102			
		103			
		104			
		105			
		106			
		107			
		108			
		109			
		110			
		111			
		112			
		113			
		114			
		115			
		116			
		117			
		118			
		119			
		120			
		121			
		122			
		123			
		124			
		125			
		126			
		127			
		128			



Dimensions in inches (millimeters) and are subject to change without notice.