M28840/26
Plug Connector
with Straight EMI/RFI Backshell

Contact Style
P, S, F, G, D or E

Military Designator | **Shell Size** | **Backshell Size Designator** | **Key Position**
1, 2, 3, 4, 5 and 6

M28840/26 C G 1 A A P 1

Material and Finish
C - Class DJ: Aluminum, Cadmium Plate, O.D. over Electroless Nickel
E - Class DJS: Corrosion Resistant Steel, Cadmium Plate, Black

Insert Arrangement

Backshell Style
A - EMI Environmental
B - Environmental

Military Shell Size	Shell Size	A Thread Class 2B	Backshell Size Designator	A Cable Entry Open	A Cable Entry Closed	E Max.	L Max.
A	11	.750-1P-.2L-DS	A	.312	.188	.938	6.500
			B	.438	.281	1.125	
			C	.562	.344	1.312	
B	13	.875-1P-.2L-DS	A	.312	.188	.938	
			B	.438	.281	1.125	
			C	.562	.344	1.312	
			D	.652	.375	1.312	7.000
C	15	1.062-1P-.2L-DS	A	.438	.281	1.125	6.500
			B	.562	.344	1.312	
			C	.625	.375	1.312	7.000
			D	.750	.438	1.593	
			E	.312	.188	.938	
D	17	1.125-1P-.2L-DS	A	.625	.375	1.312	
			B	.750	.438	1.593	
			C	.938	.625	1.750	
E	19	1.312-1P-.2L-DS	A	.625	.375	1.312	7.500
			B	.938	.625	1.750	7.625
F	23	1.500-1P-.2L-DS	A	.750	.438	1.593	7.812
			B	.938	.625	1.750	7.625
			C	1.188	.812	2.093	8.312
G	25	1.625-1P-.2L-DS	A	.938	.625	1.750	
			B	1.188	.812	2.093	
			C	1.250	.875	2.093	
			D	1.380	1.000	2.343	
H	29	1.812-1P-.2L-DS	A	1.188	.812	2.093	
			B	1.380	1.000	2.343	
J	33	2.000-1P-.2L-DS	A	1.380	1.000	2.343	
			B	1.625	1.250	2.750	8.625

Dimensions in Inches (millimeters) are subject to change without notice.

© 2011 Glenair, Inc. US Navy Approved Connectors U.S. CAGE Code 06324 Rev. 03.01.21 Printed in U.S.A.