## **EMI/RFI Shield Termination**




# Nano banding tool and bands for Series 151 and 152 connectors with banding platforms

#### THE 601-108 BAND-MASTER ATS® NANO TOOL WITH COUNTER FOR NANO BANDS



Color-coded tool handle:



Weighs 1.15 lbs., and is designed for nano flat .075" width clamping bands in a tension range from 20 to 50 lbs. Calibrate at 50 lbs.  $\pm$  3 lbs. for most shield terminations. Tool and band should never be lubricated.

	Band-Master ATS® Nano Band Selection								
	Length		Part	Number	Fits Diameter				
Bands	in.	mm.	Flat	Pre-Coiled	in.	mm.			
Short Nano	6.0	152.4	601-500	601-501	.60	15.2			
Medium Nano	9.0	228.6	601-504	601-505	.94	23.9			
Long Nano	14.0	355.6	601-508	601-509	1.8	45.7			

Cable Pull Strength for Band-Master ATS® Nano Bands										
Name Material	Material Type	Band	Band Width		Thick- ss	Tool Setting	Cable Pull			
		ln.	mm.	In.	mm.		Strength			
Nano	300 SS	0.075	1.91	.009	.23	50 ±3 lbs	50 lbs*			

<sup>\*</sup> Nano Bands are work hardened to achieve higher cable pull force

#### Short Flat 601-500 Short Precoiled 601-501

Nano Bands are precision constructed of work hardened, 300 Series SST passivate IAW AMS 2700. Short nano bands are 6.00 inches (152.4) in length and designed for use with the 601-108 Band-Master™ ATS hand banding tool or the 601-118 pneumatic banding tool. Bands should always be double wrapped and will accommodate diameters up to approximately .60 inches (15.2).

#### Medium Flat 601-504 Medium Precoiled 601-505

Nano Bands are precision constructed of work hardened, 300 Series SST passivate IAW AMS 2700. Medium nano bands are 9.00 inches (228.6) in length and designed for use with the 601-108 Band-Master™ ATS hand banding tool or the 601-118 pneumatic banding tool. Bands should always be double wrapped and will accommodate diameters up to approximately .94 inches (23.9).

### Long Flat 601-508 Long Precoiled 601-509

Nano Bands are precision constructed of work hardened, 300 Series SST passivate IAW AMS 2700. Long nano bands are 14.25 inches (361.95) in length and designed for use with the 601-108 Band-Master™ ATS hand banding tool or the 601-118 pneumatic banding tool. Bands should always be double wrapped and will accommodate diameters up to approximately 1.8 inches (45.7).

