


M29504/05 TYPE, STYLE 2 LARGE CORE METAL FERRULE SOCKET TERMINUS FOR MIL-DTL-38999 SERIES III



Part Number	Fiber Size Core/Cladding (Microns)	ØA (Microns)
181-035-600	600 Micron	610.0
181-035-1000	1000 Micron (Plastic)	1117.0

Ceramic alignment sleeve supplied with terminus. Add **K** to the end of part number development to supply with optional stainless steel alignment sleeve
e.g. 181-035-1000**K**.



NOTES

- Alignment sleeve and protective cover are supplied with terminus and may be ordered separately (see accessories table)
- Threaded protective cover must be retained using "Threadlocker Loctite 222" prior to insertion and fully seated against terminus body as shown. Contact Glenair for termination/assembly procedures.
- Insertion/extraction Tool: P/N M81969/14-03
- For socket dust cap use part number 187-019 over ferrule and 187-029 over protective cover
- Material/finish:
 - Ferrule: stainless steel/passivate
 - Alignment sleeve: zirconia ceramic or stainless steel/passivate
 - Terminus assembly, spring and cover: stainless steel/passivate

Accessories	
Part Number	Description
181-001-S	Alignment Sleeve, Split Ceramic (standard)
181-001-K	Alignment Sleeve, Split Stainless Steel
181-001-C	Protective cover