


Series 707 Micro-PSI affords PIG designers the opportunity to design out legacy large form-factor connectors with a dramatically smaller high-speed interconnect solution.




10K PSI SOLUTION

Micro-PSI

Microminiature high-speed, high-pressure connectors

The Series 707 Micro-PSI is a micro miniature 10K PSI high-pressure, high-temperature interconnect designed specifically for pipeline inspection applications in Magnetic Flux Leakage and ultrasonic pipeline inspection PIGs. The Micro-PSI insert arrangements feature high-density micro TwistPin layouts for sensor applications and high-speed Gigabit Ethernet, and a Coax contact layout for 3 GHz performance. Micro-PSI connectors are supplied as discrete plugs, or overmolded plug cordsets with rugged Viton or Polyurethane jacketing. Bulkhead and flange mount receptacles are 10K PSI open-face pressure sealed, and incorporate fused vitreous glass inserts for $<1 \times 10^{-7}$ scc He/sec hermetic performance. Serviceable O-rings on plugs and face O-rings on receptacles provide high-reliability sealing.



Application example shows the 707 Micro-PSI used to interconnect an MFL sensor to on-board PIG data storage.



Actual size!

- 10,000 PSI pressure rated
- 3 GHz Coax
- Less than 1×10^{-7} scc He/sec @ 1 ATM pressure differential
- Special-purpose high density (.056" contact spacing) intelligent inspection (PIG) connector series
- 2 Amp high-speed Gigabit Ethernet-ready
- -20° to $+150^{\circ}$ C temperature range
- High-density, small form-factor