

LIPPED STRAIGHT BOOTS FOR USE WITH BOOT ADAPTERS



Standard Boots

Pages 5-7

770-001S, 770-003S

Available in nine sizes, standard boots fit adapters from .250" (6.35) to 2.250" (57.15) diameter.



Short Boots

Pages 8-10

770-002S, 770-004S

Available in six sizes, short boots fit adapters from .450" (11.43) to 2.250" (57.15) diameter. Use where space is limited.



Long Tail Boots

Pages 11-13

770-006S

Available in seven sizes, long tail boots fit adapters from .500" (12.70) to 1.900" (48.26) diameter. Extended length provides added protection to open wire bundles or protects cable with jacket stripped further than normal.



High Ratio Boots

Pages 14-16

770-007S

Available in four sizes, high ratio boots fit adapters from .525" (13.34) to 1.650" (41.91) diameter. High ratio boots are used when the wire bundle or cable is much smaller diameter than normal.



Right Angle Boots

Pages 17-19

770-001A, 770-003A

Available in six sizes, right angle boots fit adapters from .350" (8.89) to 1.600" (40.64) diameter.

LIPLESS BOOTS FOR DIRECT ATTACHMENT TO CONNECTOR THREADS



Standard Boots

Pages 20-22

770-005S

Available in nine sizes, standard boots fit connectors from .250" (6.35) to 2.250" (57.15) diameter.



Right Angle Boots

Pages 23-25

770-005A

Available in seven sizes, right angle boots fit connectors from .250" (6.35) to 1.600" (40.64) diameter.

Dimensions in inches (millimeters) and are subject to change without notice.