



TABLE I: SHELL SIZE ORDER NUMBER

Order No.	A		B		Shell Size Ref.	Composite Torque Inch Pounds
	Ref.	(mm)	Hex	(mm)		
08	7.38	(187.5)	.750	(19.1)	08/09	40
10	7.50	(190.5)	.875	(22.2)	10/11	40
12	7.50	(190.5)	1.000	(25.4)	12/13	40
14	7.50	(190.5)	1.125	(28.6)	14/15	40
16	7.50	(190.5)	1.250	(31.8)	16/17	40
18	7.75	(196.9)	1.375	(34.9)	18/19	40
20	8.00	(203.2)	1.500	(38.1)	20/21	80
22	8.25	(209.6)	1.625	(41.3)	22/23	80
24	8.25	(209.6)	1.750	(44.5)	24/25	80
28	8.50	(215.9)	2.000	(50.8)	28	120
32	10.00	(254.0)	2.250	(57.2)	32	120
36	10.00	(254.0)	2.500	(63.5)	36	120

NOTES:

1. This backshell assembly tool is designed for Glenair composite hex coupling applications and should be used in conjunction with Glenair torque wrenches.
2. These wrenches are made of aluminum alloy with vinyl grips.
3. Metric dimensions (mm) are indicated in parentheses.