667-217 and 667-218
Series 801 Mighty Mouse Double-Start ACME Threads
Metal Protective Cover Ordering Information

Protect Connectors From Damage
Machined aluminum covers have rubber gaskets for a watertight fit.

Stainless Steel Fittings and Rings Choose small diameter eye fittings for panel attachment. Larger rings fit under the jam nut or over cable jackets. Split rings can be installed on fully assembled cables.

Polyurethane-Coated SST Wire Rope offers high strength, excellent abrasion resistance and good flexibility. Or, choose Teflon® jacket for high temperature exposure.

Braided Nylon Rope provides excellent flexibility and good abrasion resistance, and can be ordered with slip knot fittings for easy installation on any size cable.

HOW TO ORDER

Sample Part Number

667-217	-M	-G	9	04		-6
Series	**Shell Material / Finish**	**Attachment Type**	**Shell Size**	**Attachment Code**		**Attachment Length in Inches**
 667-217 Protective Cover for use with Series 801 Plugs  **667-218** Protective Cover for use with Series 801 Receptacles	**M** Aluminum / Electroless Nickel RoHS Compliant **NF** Aluminum / Cadmium with Olive Drab Chromate **ZNU** Aluminum / Zinc-Nickel with Black Chromate **MT** Aluminum / Nickel-PTFE RoHS Compliant **Z1** Stainless Steel / Passivated RoHS Compliant	**-G** Nylon Rope **-H** SST Wire Rope, Teflon® Jacket **-N** No Attachment **-S** SST Sash Chain **-SK** Nylon Rope With Slip Knot **-T** SST Wire Rope, No Jacket **-U** SST Wire Rope, Polyurethane Jacket "SST" = Stainless Steel	**6** **7**	Omit for attachment Types **N** (No Attachment) and **SK** (Slip Knot)		Omit for attachment Type **N** (No Attachment) **Example** "-6" equals six inch length
				 Small Ring	**01** – .126 (3.20) I.D. **02** – .145 (3.68) I.D. **04** – .188 (4.78) I.D. **06** – .197 (5.00) I.D.	
				 Large Ring	**14** – .385 (9.78) I.D. **15** – .445 (11.30) I.D. **16** – .570 (14.48) I.D. **17** – .635 (16.13) I.D. **18** – .695 (17.65) I.D. **19** – .885 (22.48) I.D. **20** – 1.070 (27.17) I.D. **21** – 1.135 (28.83) I.D. **22** – 1.210 (30.73) I.D. **23** – 1.275 (32.39) I.D. **24** – 1.375 (34.94) I.D.	
				 Split Ring	**50** – .420 (10.67) I.D. **52** – .480 (12.19) I.D. **54** – .635 (16.13) I.D. **56** – .745 (18.92) I.D. **58** – .885 (22.48) I.D. **60** – 1.010 (25.65) I.D. **64** – 1.125 (28.58) I.D. **68** – 1.345 (34.16) I.D.	

Dimensions in Inches (millimeters) are subject to change without notice.

© 2011 Glenair, Inc.