

## HOW TO ORDER SERIES 80 CORDSETS FOR HIGH SPEED DATA

Sample Part Number									
801-021	B	R	P	A	C	M	P	Z	- 72
Connector Series	Cable	Cable Jacket	Strain Relief	Connector End A P1	Connector End B P2	Shell Material / Finish	Protective Cover	Shell Pol. Pos.	OAL Length
<b>800-035</b> Series 800 Cordset, UNF Threaded Coupling, Hex Nut	<b>A</b> 100BASE-T Ethernet 4 Cond. UTP, OAL Shield 4 Pin Connector	<b>F</b> FEP Fluorocarbon Jacket, Translucent Blue	<b>P</b> Polyamide Overmold  <b>B</b> Aluminum Backshell	<b>A</b> Plug, with Male Pin Contacts  <b>B</b> Plug, with Female Socket Contacts	<b>A</b> Plug, with Male Pin Contacts  <b>B</b> Plug, with Female Socket Contacts	<b>M</b> Aluminum / Electroless Nickel  <b>NF</b> Aluminum / Cadmium with Olive Drab Chromate	<b>P</b> Metal Protective Covers Included  <b>N</b> No Covers Supplied	<b>N</b> Normal  <b>X</b> Pos. X  <b>Y</b> Pos. Y  <b>Z</b> Pos. Z	Overall Length In Inches  12 Inch Min.
<b>801-021</b> Series 801 Cordset, Double- Start Threaded Coupling	<b>B</b> 100BASE-T Ethernet Quad, OAL Shield, 4 Pin Connector	<b>P</b> Low Smoke/ Zero Halogen Polyurethane Jacket, Black	<b>H</b> Heat-Shrink Boot, Low Smoke/ Zero Halogen	<b>C</b> Receptacle, with Male Pin Contacts  <b>D</b> Receptacle, with Female Socket Contacts	<b>C</b> Receptacle, with Male Pin Contacts  <b>D</b> Receptacle, with Female Socket Contacts	<b>ZN</b> Aluminum / Zinc-Nickel with Olive Drab Chromate  <b>ZNU</b> Aluminum / Zinc-Nickel with Black Chromate			
<b>803-007</b> Series 803 Cordset, Push- Pull With Bayonet Lock Coupling	<b>C</b> 1000BASE- T Gigabit Ethernet 8 Cond. UTP, OAL Shield, 10 Pin Connector					<b>Z1</b> Stainless Steel / Passivated			
<b>804-013</b> Series 804 Cordset, Quick- Disconnect Push- Pull	<b>D</b> IEEE 1394 Hi-Speed Quad 110 Ohm, 4 Pin Connector				<b>N</b> No Connector (Single- Ended)				
<b>805-007</b> Series 805 Cordset, Tri- Start Threaded Coupling with Ratchet and Ground Spring	<b>E</b> USB 2.0, Two #22 Power, One STP #26  <b>F</b> Two STP, 100 Ohm, OAL Shield, 4 Pin Connector  <b>G</b> Four STP, 100 Ohm, OAL Shield, 10 Pin Connector								