

MICRO-CRIMP RECTANGULAR CONNECTORS

Series 790 High-Density




790-042

PCB Plug, 90° Tails

- ◆ 90° PCB termination
- ◆ Socket contacts

SERIES 790 HIGH-DENSITY



Shell Size	A Max	B ± .005 (0.1)	C Max	D Max	E Max	F Min
	in	mm	in	mm	in	mm
A	.805	20.4	.565	14.4	.335	8.5
B	.955	24.3	.715	18.2	.485	12.3
C	1.105	28.1	.865	22.0	.635	16.1
D	1.205	30.6	.965	24.5	.735	18.7
E	1.355	34.4	1.115	28.3	.885	22.5
F	1.505	38.2	1.265	32.1	1.035	26.3
G	1.455	37.0	1.215	30.9	1.010	25.7
H	2.185	55.5	1.800	45.7	1.385	35.2
J	1.855	47.1	1.615	41.0	1.390	35.3
K	2.255	57.3	2.015	51.2	1.795	45.6
L	2.430	61.7	2.036	51.7	1.623	41.2
M	2.575	65.4	2.200	55.9	1.675	42.5

Application Note

PCB Footprints

See Section **G** for PC board layouts.


Straight tails: pages **G-1** – **G-9**
90° tails: pages **G-10** – **G-20**

Application Note

Panel Mounting

For panel mounting, specify connector without jackposts. Use rear panel mount jackpost **799-119**. See page **F-20** for jackpost ordering information and panel cutout dimensions.

JACKPOST OPTIONS




N

No Jackposts

Connector has blind threaded holes, .150 (3.8) minimum depth.

Size A-G, J, K = 4-40 UNC-2B
Size H, L = 6-32 UNC-2B
Size M = 8-32 UNC-2B



P

Jackposts

Non-removable.

Size A-G, J, K = 2-56 UNC-2B
Size H, L = 4-40 UNC-2B
Size M = 6-32 UNC-2B

MICRO-CRIMP RECTANGULAR CONNECTORS

Series 790 High-Density

SERIES™
790
HD


Insert Arrangements

SERIES 790 HIGH-DENSITY

INSERT ARRANGEMENTS				
Insert Arr.	No. of Contacts			
	#23	#16	#12	#8
A-5	5			
B-2P2		2		
B-9	9			
C-13	13			
D-15	15			
D-3P3		3		
D-7P2	5	2		
E-11P2	9	2		
E-19	19			
E-7P3	4	3		
F-14P3	11	3		
F-15P2	13	2		
F-23	23			
F-5P5		5		
G-13P2	11		2	
G-21P1	20		1	
G-3P3			3	
G-33	33			
H-10P4	6		4	
H-29P7	22	7		
H-36P2	34		2	
H-51P1	50		1	
H-54P2	52	2		
H-5P5			5	
H-66	66			
J-17P4	13	4		
J-25P2	23	2		
J-33	33			
J-7P7		7		
K-27P4	23	4		
K-35P2	33	2		
K-43	43			
K-9P9		9		
L-22P4	18		4	
L-48P2	46		2	
L-6P6			6	
L-78	78			
M-17P17		17		
M-102	102			
M-4P4				4
N-13P13			13	
N-153	153			

⚠ Cavity Numbers

Cavity numbers shown are for mating face of receptacle (pin) connector. Plug (socket) numbers are reversed.



MICRO-CRIMP RECTANGULAR CONNECTORS

Series 790 High-Density



Specifications

CONSTRUCTION

Contacts	Copper alloy, gold over nickel finish
Hood, socket contact	Stainless steel, passivated
Clip, contact retaining	Beryllium copper
Clip, insert retaining	Beryllium copper
Insulators	High performance thermoplastic
Grommet and face seal	Fluorosilicone/silicone blend
Shell	Aluminum
Gasket, panel	Cho-Seal 1287 Ag/Al filled fluorosilicone
EMI spring	Stainless steel, gold plated
EMI shroud (90° PCB)	Aluminum
Encapsulant (PCB)	Epoxy
Hardware	Stainless steel, passivated

RATINGS

Voltage (DWV)	Size 23 contacts: 750 VAC Size 8, 12 and 16 contacts: 1800 VAC	
Current Rating	Contact Size	Current (A)
	#23	5
	#16	13
	#12	23
	#8	46
Operating Temperature	-65 to +150 °C	
Ingress Protection	IP67	
Durability	500 mating cycles	

PRODUCT SPECIFICATIONS

Description	Requirement	Procedure
Contact Resistance	SAE AS39029 Table 5	EIA-364-06
Low Level Contact Resistance	SAE AS39029 Table 4	EIA-364-23
Insulation Resistance	5000 megohms minimum	EIA-364-21
Dielectric Withstanding Voltage	#23 contacts 750 volts, #8, 12 & 16 contacts 1800 volts	EIA-364-20
Current Rating	#23: 5A, #16: 13A, #12: 23A, #8: 46A	EIA-364-70 Method 1
Shell-to-shell Resistance	2.5 millivolt drop maximum (connector with EMI spring)	EIA-364-83
Shielding Effectiveness	100 – 1000MHz: >50 dB, 1 – 4GHz: >41dB, 4 – 10GHz: >35 dB	EIA-364-66
Ingress Protection	IP67 rating	IEC-60529
Vibration, Sine	20 g	EIA-364-28 Test Condition IV
Vibration, Random	16.91 g rms	EIA-364-28 Test Condition V Letter E
Mechanical Shock	300 g	EIA-364-27 Condition D
Thermal Shock	-65 to +150 °C	EIA-364-32 Test Condition IV
Humidity	10 Day, +25 to +65° C	EIA-364-31 Method IV, Step 7b vibration deleted
Mechanical Durability	500 mating cycles	EIA-364-09
Salt Spray	Plating code M: 48 hours, MT, ZR, N, TZ: 500 hours	EIA-364-26
Solderability, PC Tail Contacts	95% solder coverage. Smooth, bright and even finish.	EIA-364-52 Category 3, 8 hours steam aging
Resistance To Soldering Heat	260° C, 10 seconds	EIA-364-56
Fluid Immersion	No damage from immersion in various fuels and oils.	EIA-364-10
Altitude Immersion	75,000 feet	EIA-364-03
Contact Retention	MIL-DTL-38999 Table XVIII	EIA-364-29
Contact Separation Force	SAE AS39029 Table 9	EIA-364-37
Magnetic Permeability	2 μ maximum.	EIA-364-54

MICRO-CRIMP RECTANGULAR CONNECTORS

Series 790 High-Density



Series 790 Material and Finish Options

SERIES 790 HIGH-DENSITY

The Series 790 Micro-Crimp® connector is available in five preferred finishes: electroless nickel, nickel-PTFE, tin-zinc, cadmium, and zinc-nickel.

Additional material and finish options are available. Replace the preferred plating code with the alternate code from the table below.

SERIES 790 SHELL FINISH OPTIONS

	Electroless Nickel	Nickel-PTFE	Tin-Zinc	Olive Drab Cadmium	Black Zinc-Nickel
Glenair Code	M	MT	TZ	N	ZR
Corrosion Resistance	Fair	Excellent	Excellent	Excellent	Excellent
Salt Spray Hours	48	500	500	500	500
Conductivity	Excellent	Excellent	Very Good	Very Good	Very Good
RoHS Compliant ⁽¹⁾	Yes	Yes	Yes	No	Yes

⁽¹⁾ Does not contain cadmium or hexavalent chromium. Meets EU requirements.

TIN-ZINC PLATING

The United States Department of Defense (DOD) has mandated the elimination of cadmium from DOD weapons systems because of toxicity concerns. The European Union has also restricted the use of cadmium on electronics equipment (RoHS). Tin-Zinc is a RoHS cadmium-free sacrificial finish that offers high conductivity and shielding performance, corrosion resistance, solderability, and proven compatibility with legacy cadmium and zinc-nickel finishes. Tin-Zinc is DLA-qualified and RoHS compliant.

ALTERNATE SHELL MATERIAL AND FINISH CODES

Code	Shell Material	Shell Finish	Finish Specification	Salt Spray Hrs.	Electrical Conductivity	RoHS ⁽¹⁾
C	Alum	Anodize, Black	MIL-PRF-8625	48	Non-Conductive	✓
E⁽²⁾	Alum	Chem Film, Gold	MIL-DTL-5541	168	Conductive	
J	Alum	Cadmium, Yellow	AMS-QQ-P-416	500	Conductive	
Z1	SST	Passivate	AMS2700	500	Conductive	✓
Z2	Alum	Gold	MIL-DTL-45204	48	Conductive	✓
ZM	SST	Electroless Nickel	AMS-C-26074	500	Conductive	✓
ZMT	SST	Nickel-PTFE	AMS2454	1000	Conductive	✓
ZW	SST	Cadmium, Olive Drab	AMS-QQ-P-416	500	Conductive	
ZZR	SST	Zinc-Nickel, Black	ASTM B841	500	Conductive	✓

⁽¹⁾ Does not contain cadmium or hexavalent chromium. Meets EU requirements.

⁽²⁾ Maximum temperature = +125°C

SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791


SERIES
79
TM

90° PCB Footprints for Series 790 and 791 Connectors




PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS

PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032




A-5

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




B-2P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




B-9

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




C-13

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



D-15

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791





90° PCB Footprints for Series 790 and 791 Connectors

PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS




PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032




D-3P3

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




D-7P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




E-11P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



E-19

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791


SERIES
79
TM

90° PCB Footprints for Series 790 and 791 Connectors





PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS

PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032




Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.


Non-symmetrical arrangement
Pattern must be reversed for use with plug (socket) connector.



Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791





90° PCB Footprints for Series 790 and 791 Connectors



PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS




PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032





Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791

SERIES
79
TM


90° PCB Footprints for Series 790 and 791 Connectors



PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS


PCB hole patterns are shown for the **component mounting side** of the circuit board.

Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032





G-33

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.





H-10P4

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




H-29P7

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



H-36P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791





90° PCB Footprints for Series 790 and 791 Connectors

PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS





PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032





H-51P1

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




H-54P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




H-5P5

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



H-66

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



PCB FOOTPRINTS FOR SERIES 790, 791

SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791


SERIES
79
TM

90° PCB Footprints for Series 790 and 791 Connectors




PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS

PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032




J-17P4

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




J-25P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




J-33

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



J-7P7

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791




90° PCB Footprints for Series 790 and 791 Connectors

PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS




PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032




K-27P4

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




K-35P2

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




K-43

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



K-9P9

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




PCB FOOTPRINTS FOR SERIES 790, 791



PCB FOOTPRINTS FOR SERIES 790, 791

90° PCB Footprints for Series 790 and 791 Connectors



CONNECTOR ORIENTATION





Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



SERIES 79 MICRO-CRIMP RECTANGULAR CONNECTORS

PCB Footprints for Series 790 and 791





90° PCB Footprints for Series 790 and 791 Connectors

PCB FOOTPRINTS FOR SERIES 790 AND 791 CONNECTORS WITH 90° TAILS





PCB hole patterns are shown for the *component mounting side* of the circuit board.
Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032





M-17P17

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.





M-102

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.




M-4P4

Contact numbers are mating face of pin connector.
Socket connector contact numbers are reversed.



N-13P13



Contact numbers are mating face of pin connector. Socket connector contact numbers are reversed.



PCB FOOTPRINTS FOR SERIES 790, 791

90° PCB Footprints for Series 790 and 791 Connectors

Circuit board drill patterns for Series 790 and 791 connectors with 90° tails: 790-036, 790-037, 790-041, 790-042, 791-011, 791-012, 791-016, 791-032



Contact numbers are mating face of pin connector. Socket connector contact numbers are reversed.

