

MIL-DTL-38999 Series I Type Connector performance specifications

HERMETIC CONNECTORS

REQUIREMENT	PERFORMANCE SPECIFICATIONS																																																												
Insert Arrangements	(Meets MIL-DTL-38999, paragraph 3.4.1.4) For hermetic connectors, the engaging end of pin and socket contacts shall be located within .004 inch (0.10 mm) diameter of true position. Test voltages for service ratings shall be as specified in table below																																																												
	TEST VOLTAGES, AC RMS, 60 HZ (UNMATED)																																																												
	<table><tr><th rowspan="2">Altitude</th><th colspan="2">Service Rating M</th><th colspan="2">Service Rating N</th><th colspan="2">Service Rating I</th><th colspan="2">Service Rating II</th></tr><tr><th>Mated</th><th>Unmated</th><th>Mated</th><th>Unmated</th><th>Mated</th><th>Unmated</th><th>Mated</th><th>Unmated</th></tr><tr><td>Sea level</td><td>1300</td><td>1300</td><td>1000</td><td>1000</td><td>1800</td><td>1800</td><td>2300</td><td>2300</td></tr><tr><td>50,000 feet</td><td>800</td><td>550</td><td>600</td><td>400</td><td>1000</td><td>600</td><td>1000</td><td>800</td></tr><tr><td>70,000 feet</td><td>800</td><td>350</td><td>600</td><td>260</td><td>1000</td><td>400</td><td>1000</td><td>500</td></tr><tr><td>100,000 feet</td><td>800</td><td>200</td><td>600</td><td>200</td><td>1000</td><td>200</td><td>1000</td><td>200</td></tr></table>	Altitude	Service Rating M		Service Rating N		Service Rating I		Service Rating II		Mated	Unmated	Mated	Unmated	Mated	Unmated	Mated	Unmated	Sea level	1300	1300	1000	1000	1800	1800	2300	2300	50,000 feet	800	550	600	400	1000	600	1000	800	70,000 feet	800	350	600	260	1000	400	1000	500	100,000 feet	800	200	600	200	1000	200	1000	200							
	Altitude		Service Rating M		Service Rating N		Service Rating I		Service Rating II																																																				
		Mated	Unmated	Mated	Unmated	Mated	Unmated	Mated	Unmated																																																				
	Sea level	1300	1300	1000	1000	1800	1800	2300	2300																																																				
	50,000 feet	800	550	600	400	1000	600	1000	800																																																				
70,000 feet	800	350	600	260	1000	400	1000	500																																																					
100,000 feet	800	200	600	200	1000	200	1000	200																																																					
Supported Wire Size	(Per MIL-DTL-38999, paragraph 3.4.3.1)																																																												
	<table><tr><td>Contact Size</td><td>23-22</td><td>22D</td><td>20</td><td>16</td><td>12</td><td>10</td></tr><tr><td>Wire Gauge</td><td>26, 24, 22</td><td>28, 26, 24, 22</td><td>24, 22, 20</td><td>20, 18, 16</td><td>14, 12</td><td>10</td></tr></table>	Contact Size	23-22	22D	20	16	12	10	Wire Gauge	26, 24, 22	28, 26, 24, 22	24, 22, 20	20, 18, 16	14, 12	10																																														
Contact Size	23-22	22D	20	16	12	10																																																							
Wire Gauge	26, 24, 22	28, 26, 24, 22	24, 22, 20	20, 18, 16	14, 12	10																																																							
Thermal Shock	(Meets MIL-DTL-38999, paragraph 3.7) After cycling the connector between two water baths of approximately 1 cubic foot, not to exceed +4°C for the first and no less than +90°C for the second, it will meet all applicable electrical and mechanical requirements.																																																												
Air Leakage	(Meets MIL-DTL-38999, paragraph 3.10) There shall be no evidence of leakage in excess of .01 micron ft³/h (1E-7 cm³/s)																																																												
Coupling and Uncoupling Torque	(Meets MIL-DTL-38999, paragraph 3.11) Coupling torque for mating and the uncoupling torque for unmating of counterpart plugs and receptacles, mating of connectors to and from protective covers, and mating plugs to and from dummy stowage receptacles, shall meet the requirements in Coupling and Uncoupling Torque table.																																																												
	COUPLING AND UNCOUPLING TORQUE																																																												
	<table><tr><th>Shell size</th><th>Maximum engagement and disengagement inch/pound</th><th>Minimum Disengagement inch/pound</th><th>Shell size</th><th>Maximum engagement and disengagement inch/pound</th><th>Minimum Disengagement inch/pound</th></tr><tr><td>8</td><td>8</td><td>2</td><td>17</td><td>24</td><td>3</td></tr><tr><td>9</td><td>8</td><td>2</td><td>18</td><td>28</td><td>5</td></tr><tr><td>10</td><td>12</td><td>2</td><td>19</td><td>28</td><td>3</td></tr><tr><td>11</td><td>12</td><td>2</td><td>20</td><td>32</td><td>6</td></tr><tr><td>12</td><td>16</td><td>2</td><td>21</td><td>32</td><td>5</td></tr><tr><td>13</td><td>16</td><td>2</td><td>22</td><td>36</td><td>7</td></tr><tr><td>14</td><td>20</td><td>4</td><td>23</td><td>36</td><td>5</td></tr><tr><td>15</td><td>20</td><td>3</td><td>24</td><td>36</td><td>7</td></tr><tr><td>16</td><td>24</td><td>4</td><td>25</td><td>40</td><td>5</td></tr></table>	Shell size	Maximum engagement and disengagement inch/pound	Minimum Disengagement inch/pound	Shell size	Maximum engagement and disengagement inch/pound	Minimum Disengagement inch/pound	8	8	2	17	24	3	9	8	2	18	28	5	10	12	2	19	28	3	11	12	2	20	32	6	12	16	2	21	32	5	13	16	2	22	36	7	14	20	4	23	36	5	15	20	3	24	36	7	16	24	4	25	40	5
	Shell size	Maximum engagement and disengagement inch/pound	Minimum Disengagement inch/pound	Shell size	Maximum engagement and disengagement inch/pound	Minimum Disengagement inch/pound																																																							
	8	8	2	17	24	3																																																							
	9	8	2	18	28	5																																																							
	10	12	2	19	28	3																																																							
	11	12	2	20	32	6																																																							
	12	16	2	21	32	5																																																							
	13	16	2	22	36	7																																																							
	14	20	4	23	36	5																																																							
15	20	3	24	36	7																																																								
16	24	4	25	40	5																																																								
Durability	(Meets MIL-DTL-38999, paragraph 3.12) Not applicable to lanyard release plugs. No electrical or mechanical defects after 500 cycles of engagement and disengagement.																																																												
Insulation Resistance	(Meets MIL-DTL-38999, paragraph 3.14.1) At Ambient Temperature insulation resistance between any pair of contacts and between any contact and the shell shall be greater than 5,000 megohms. Insulation resistance after altitude immersion shall be 1,000 megohms minimum. Insulation resistance after humidity shall be 100 megohms minimum. IAW EIA-364-21. (Meets MIL-DTL-38999, paragraph 3.14.2) At Elevated Temperature, unmated connectors shall be tested in accordance with test procedure EIA/ECA-364-21																																																												

MIL-DTL-38999 Series I Type Connector performance specifications

REQUIREMENT	PERFORMANCE SPECIFICATIONS					
Dielectric Withstanding Voltage	<i>(Meets MIL-DTL-38999, paragraph 3.15)</i> Wired, unmated connector, maximum leakage current shall be 2 milliamperes, and there shall be no evidence of electric breakdown or flashover. IAW EIA-364-20 method A. Magnitude of the test voltage shall be as specified per insert arrangement requirement, Test Voltages Table (See MIL-STD-1560 for service rating of insert arrangement).					
Insert Retention	<i>(Meets MIL-DTL-38999, paragraph 3.16)</i> When tested IAW EIA-364-35, unmated connectors shall retain their inserts in their proper location in the shell and there shall be no evidence of cracking, breaking, separation from the shell, or loosening of parts when subjected to 100 PSI (25 PSI minimum) force.					
Salt Spray (Corrosion)	<i>(Meets MIL-DTL-38999, paragraph 3.17)</i> When tested in accordance with EIA-364-26, meets appropriate electrical and mechanical requirements and shows no exposure of base metal after 500 hours of salt spray.					
Contact Resistance at 25° C	<i>(Meets MIL-DTL-38999, paragraph 3.18) Hermetic connectors with sockets only</i> Contacts in the mated condition shall meet the contact resistance requirements of the table shown below. Appropriate compensation may be made for resistance in the measured value which is due to an additional length of wire included in the measurement.					
	Class	Contact Size	Wire Size	Test Amperes	Millivolt Drop Maximum	
					Initial	After Conditioning
	H, N and Y	12	12	17	85	100
		16	16	10	85	100
		20	20	5	60	75
		22D	22	3	85	95
23-22	22	3	85	95		
Bayonet Coupling Pin Strength	<i>(Meets MIL-DTL-38999, paragraph 3.21)</i> Applicable to series I and II only. Bayonet coupling pins shall withstand a load of 50 +5/-0 pounds without displacement or perceptible loosening of coupling pins.					
Environmental Contact Retention Connectors	<i>(Meets MIL-DTL-38999, paragraph 3.24)</i> The axial displacement of the contact shall not exceed .012 inch (0.30 mm). No damage to contacts or inserts shall result.					
Vibration	<i>(Meets MIL-DTL-38999, paragraph 3.27)</i> There shall be no electrical discontinuity and there shall be no disengagement of mated connectors, backing off of the coupling mechanism, evidence of cracking, breaking, or loosening of parts.					
Shock	<i>(Meets MIL-DTL-38999, paragraph 3.28)</i> There shall be no electrical discontinuity and there shall be no disengagement of mated connectors, evidence of cracking, breaking, or loosening of parts. Standard shock (all series). Connectors shall be tested in accordance with test procedure EIA-364-27 and any additional details noted. High-impact shock. Applicable to series I, III and IV only. Wired and mated connectors shall be tested in accordance with MIL-S-901, grade A and in accordance with any modifications or additions noted. The wire bundle shall be provided with a straight, environmental, backshell, category 2B in accordance with SAE-AS85049, the longest length available per shell size. Discontinuity monitoring shall be performed in accordance with EIA-364-46.					

MIL-DTL-38999 Series I Type Connector performance specifications

REQUIREMENT	PERFORMANCE SPECIFICATIONS																																																																					
EMI Shielding	(Meets MIL-DTL-38999, paragraph 3.32) EMI shielding, low frequencies. Applicable frequency range is 100 to 1,000 MHz only. EMI shielding, high frequencies. Applicable frequency range is 1,000 to 10,000 MHz only. The EMI shielding effectiveness of mated connectors with EMI backshells shall be measured using the mode-stirred technique in accordance with test procedure EIA-364-66. EMI shielding capabilities of mated shells with spring fingers shall not be less than that specified in table at the specified frequencies below.																																																																					
	<table><tr><th rowspan="2">Frequency MHz</th><th colspan="4">Leakage Attenuation (dB) Minimum</th></tr><tr><th>Series I</th><th>Series II</th><th>Series III & IV (Class N)</th><th>Series III & IV (Class H & Y)</th></tr><tr><td>100</td><td>90</td><td>65</td><td>90</td><td>80</td></tr><tr><td>200</td><td>88</td><td>60</td><td>88</td><td>75</td></tr><tr><td>300</td><td>88</td><td>55</td><td>88</td><td>73</td></tr><tr><td>400</td><td>87</td><td>55</td><td>87</td><td>71</td></tr><tr><td>800</td><td>85</td><td>45</td><td>85</td><td>66</td></tr><tr><td>1,000</td><td>85</td><td>45</td><td>85</td><td>65</td></tr><tr><td>1,500</td><td>69</td><td>—</td><td>76</td><td>59</td></tr><tr><td>2,000</td><td>65</td><td>—</td><td>70</td><td>55</td></tr><tr><td>3,000</td><td>61</td><td>—</td><td>69</td><td>52</td></tr><tr><td>4,000</td><td>58</td><td>—</td><td>68</td><td>50</td></tr><tr><td>6,000</td><td>55</td><td>—</td><td>66</td><td>48</td></tr><tr><td>10,000</td><td>50</td><td>—</td><td>65</td><td>45</td></tr></table>	Frequency MHz	Leakage Attenuation (dB) Minimum				Series I	Series II	Series III & IV (Class N)	Series III & IV (Class H & Y)	100	90	65	90	80	200	88	60	88	75	300	88	55	88	73	400	87	55	87	71	800	85	45	85	66	1,000	85	45	85	65	1,500	69	—	76	59	2,000	65	—	70	55	3,000	61	—	69	52	4,000	58	—	68	50	6,000	55	—	66	48	10,000	50	—	65	45
	Frequency MHz		Leakage Attenuation (dB) Minimum																																																																			
		Series I	Series II	Series III & IV (Class N)	Series III & IV (Class H & Y)																																																																	
	100	90	65	90	80																																																																	
	200	88	60	88	75																																																																	
	300	88	55	88	73																																																																	
	400	87	55	87	71																																																																	
	800	85	45	85	66																																																																	
	1,000	85	45	85	65																																																																	
	1,500	69	—	76	59																																																																	
	2,000	65	—	70	55																																																																	
	3,000	61	—	69	52																																																																	
	4,000	58	—	68	50																																																																	
6,000	55	—	66	48																																																																		
10,000	50	—	65	45																																																																		
Fluid Immersion	(Meets MIL-DTL-38999, paragraph 3.34) Designed to function in all fluids encountered in any modern military or aerospace environment. Tested in accordance with test procedure EIA-364-10. Connectors shall be tested for coupling torque and dielectric withstanding voltage at sea level within 3 hours of fluid immersion cycles.																																																																					
Contact engagement and separating force	(Meets MIL-DTL-38999, paragraph 3.42) Applicable to hermetic connectors with sockets only When tested as specified in 4.5.38, contact engagement and separating forces shall be within the limits specified in SAE-AS39029.																																																																					
Resistance to Probe Damage	(Meets MIL-DTL-38999, paragraph 3.43) Applicable to hermetic connectors with sockets only Contacts shall withstand the bending moment and depth of test probe insertion without evidence of damage that would interfere with the mechanical or electrical performance.																																																																					
Fungus	(Meets MIL-DTL-38999, paragraph 4.2.2) Materials used in the construction of these connectors shall be fungus inert per certification of method 508.4 of MIL-STD-810.																																																																					