


290-009 Cover for Standard Plug (Non-Scoop-Proof) Series 22 Connectors



How To Order Plug Cover				
Sample Part Number	290-009	S	18	03- 5
Series - Shell Style	290-009 = Standard Plug			
Attachment Type	See Table III			
Shell Size	See Table I			
Dash No.	See Table II or Table IV			
Attachment Length	5 = 5 inches			

NOTES:

1. Assembly identified with manufacturer's name and P/N, space permitting.
2. Protective cover is capable of hydrostatic sealing pressures to 5000 PSI, when fully mated with counterpart plug.
3. Material/finish:
Cover, hardware & split ring - 300 series stainless steel/passivate
Wire rope - CRES, see Table III/passivate
O-ring - nitrile/n.a.

Table I: Dimensions				
Shell Size	A Max	B Max	C Thread Class 2A	Piston O-Ring Size*
10	0.900 (22.9)	0.602 (15.3)	.750 -1P-.1L	2-014
12	1.025 (26.0)	0.727 (18.5)	.875 -1P-.1L	2-016
14	1.150 (29.2)	0.852 (21.6)	1.000 -1P-.1L	2-018
16	1.275 (32.4)	0.977 (24.8)	1.125 -1P-.1L	2-020
18	1.525 (38.7)	1.102 (28.0)	1.250 -1P-.1L	2-022
20	1.650 (41.9)	1.227 (31.2)	1.375 -1P-.1L	2-024
22	1.775 (45.1)	1.352 (34.3)	1.500 -1P-.1L	2-026
24	1.900 (48.3)	1.477 (37.5)	1.625 -1P-.1L	2-028

* Reference piston o-ring P/N when purchasing replacement rings

Table III: Attachment Type					
Sym	Attachment	Sym	Attachment	Sym	Attachment
D	Bead chain, CRES, passivated, with terminal	G	Bead chain, CRES, passivated, no terminal	T	Wire rope, no jacket, w/terminal
E	Link chain, CRES, passivated, with clevis terminal	H	Wire rope, Fluoropolymer jacket w/ terminal	K	Nylon rope
F	Wire rope, nylon jacket w/terminal	N	Attachment omitted	S	#8 Sash chain, CRES, passivate
		R	Wire rope, pvc jacket w/terminal	U	Wire rope, polyurethane jacket, with terminal

Table II: Solid Ring Dia.	
Dash No	D Dia
01	0.125 (31.8)
02	0.140 (3.6)
03	0.167 (4.2)
04	0.182 (4.6)
05	0.191 (4.9)
06	0.197 (5.0)

Table IV: Split Ring Dia.			
Dash No	E Dia	Dash No	E Dia
50	0.425 (10.8)	66	1.250 (31.8)
52	0.485 (12.3)	68	1.350 (34.3)
54	0.640 (16.3)	70	1.375 (34.9)
56	0.750 (19.1)	72	1.485 (37.7)
58	0.890 (22.6)	74	1.625 (41.3)
60	1.015 (25.8)	76	1.750 (44.5)
62	1.095 (27.8)	78	1.875 (47.6)
64	1.130 (28.7)	80	1.980 (50.3)
		82	2.060 (52.3)

